

[Close this window](#)

SDS

Common Name: HYDROFORCE STAINLESS STEEL CLEANER AND POLISH 14424**Manufacturer:** CRC**SDS Revision Date:** 4/30/2015**SDS Format:** GHS-US**Item Number(s):** 4JB52**Manufacturer Model Number(s):**

SDS Table of Contents

Click the desired link below to jump directly to that section in the SDS.

- [1. IDENTIFICATION](#)
- [2. HAZARD\(S\) IDENTIFICATION](#)
- [3. COMPOSITION/INFORMATION ON INGREDIENTS](#)
- [4. FIRST-AID MEASURES](#)
- [5. FIRE-FIGHTING MEASURES](#)
- [6. ACCIDENTAL RELEASE MEASURES](#)
- [7. HANDLING AND STORAGE](#)
- [8. EXPOSURE CONTROLS/PERSONAL PROTECTION](#)
- [9. PHYSICAL AND CHEMICAL PROPERTIES](#)
- [10. STABILITY AND REACTIVITY](#)
- [11. TOXICOLOGICAL INFORMATION](#)
- [12. ECOLOGICAL INFORMATION](#)
- [13. DISPOSAL CONSIDERATIONS](#)
- [14. TRANSPORT INFORMATION](#)
- [15. REGULATORY INFORMATION](#)
- [16. OTHER INFORMATION, INCLUDING DATE OF PREPARATION](#)

CRC (R*)

SAFETY DATA SHEET

1. IDENTIFICATION



PRODUCT IDENTIFIER: HYDROFORCE(R*) STAINLESS STEEL CLEANER AND POLISH

OTHER MEANS OF IDENTIFICATION:

PRODUCT CODE: 14424

RECOMMENDED USE: STAINLESS STEEL CLEANER

RECOMMENDED RESTRICTIONS: NONE KNOWN.

MANUFACTURER/IMPORTER/SUPPLIER/DISTRIBUTOR INFORMATION:

MANUFACTURED OR SOLD BY:

COMPANY NAME: CRC INDUSTRIES, INC.

ADDRESS:
885 LOUIS DR.
WARMINSTER, PA 18974
US

TELEPHONE:
GENERAL INFORMATION: 215-674-4300
TECHNICAL ASSISTANCE: 800-521-3168

CUSTOMER SERVICE: 800-272-4620

24-HOUR EMERGENCY (CHEMTREC):
800-424-9300 (US)
703-527-3887 (INTERNATIONAL)

WEBSITE: WWW.CRCINDUSTRIES.COM

2. HAZARD(S) IDENTIFICATION



PHYSICAL HAZARDS:
GASES UNDER PRESSURE: LIQUEFIED GAS

HEALTH HAZARDS:
SERIOUS EYE DAMAGE/EYE IRRITATION: CATEGORY 1

ENVIRONMENTAL HAZARDS:
HAZARDOUS TO THE AQUATIC ENVIRONMENT, ACUTE HAZARD: CATEGORY 3
HAZARDOUS TO THE AQUATIC ENVIRONMENT, LONG-TERM HAZARD: CATEGORY 3

OSHA DEFINED HAZARDS: NOT CLASSIFIED.

LABEL ELEMENTS:
GAS CYLINDER
CORROSION

SIGNAL WORD: DANGER

HAZARD STATEMENT:
CONTAINS GAS UNDER PRESSURE; MAY EXPLODE IF HEATED. CAUSES SERIOUS EYE DAMAGE. HARMFUL TO AQUATIC LIFE. HARMFUL TO AQUATIC LIFE WITH LONG LASTING EFFECTS.

PRECAUTIONARY STATEMENT:

PREVENTION:
DO NOT PUNCTURE OR INCINERATE CONTAINER. DO NOT EXPOSE TO HEAT OR STORE AT TEMPERATURES ABOVE 49 DEG. C/120 DEG. F. USE WITH ADEQUATE VENTILATION. OPEN DOORS AND WINDOWS OR USE OTHER MEANS TO ENSURE A FRESH AIR SUPPLY DURING USE AND WHILE PRODUCT IS DRYING. IF YOU EXPERIENCE ANY SYMPTOMS LISTED ON THIS LABEL, INCREASE VENTILATION OR LEAVE THE AREA. WEAR EYE/FACE PROTECTION. AVOID RELEASE TO THE ENVIRONMENT.

RESPONSE:

IF IN EYES:
RINSE CAUTIOUSLY WITH WATER FOR SEVERAL MINUTES. REMOVE CONTACT LENSES, IF PRESENT AND EASY TO DO. CONTINUE RINSING. IMMEDIATELY CALL A POISON CENTER/DOCTOR.

STORAGE:
PROTECT FROM SUNLIGHT. STORE IN A WELL-VENTILATED PLACE. EXPOSURE TO HIGH TEMPERATURE MAY CAUSE CAN TO BURST.

DISPOSAL:

DISPOSE OF CONTENTS/CONTAINER IN ACCORDANCE WITH LOCAL/REGIONAL/NATIONAL REGULATIONS.

HAZARD(S) NOT OTHERWISE CLASSIFIED (HNOC): NONE KNOWN.

3. COMPOSITION/INFORMATION ON INGREDIENTS

MIXTURES:

CHEMICAL NAME	COMMON NAME AND SYNONYMS	CAS NUMBER	%
WATER		7732-18-5	50 - 60
LIGHT MINERAL OIL		8042-47-5	20 - 30
DISTILLATES (PETROLEUM), HYDROTREATED LIGHT		64742-47-8	5 - 10
LIQUEFIED PETROLEUM GAS		68476-86-8	5 - 10
DIOCTYL SODIUM SULFOSUCCINATE		577-11-7	1 - 3

SPECIFIC CHEMICAL IDENTITY AND/OR PERCENTAGE OF COMPOSITION HAS BEEN WITHHELD AS A TRADE SECRET.

4. FIRST-AID MEASURES

INHALATION:

REMOVE VICTIM TO FRESH AIR AND KEEP AT REST IN A POSITION COMFORTABLE FOR BREATHING. CALL A PHYSICIAN IF SYMPTOMS DEVELOP OR PERSIST.

SKIN CONTACT:

WASH OFF IMMEDIATELY WITH SOAP AND PLENTY OF WATER. GET MEDICAL ATTENTION IF IRRITATION DEVELOPS AND PERSISTS.

EYE CONTACT:

IMMEDIATELY FLUSH EYES WITH PLENTY OF WATER FOR AT LEAST 15 MINUTES. REMOVE CONTACT LENSES, IF PRESENT AND EASY TO DO. CONTINUE RINSING. GET MEDICAL ATTENTION IMMEDIATELY.

INGESTION:

CALL A PHYSICIAN OR POISON CONTROL CENTER IMMEDIATELY. RINSE MOUTH.

MOST IMPORTANT SYMPTOMS/EFFECTS, ACUTE AND DELAYED:

SEVERE EYE IRRITATION. SYMPTOMS MAY INCLUDE STINGING, TEARING, REDNESS, SWELLING, AND BLURRED VISION. PERMANENT EYE DAMAGE INCLUDING BLINDNESS COULD RESULT.

INDICATION OF IMMEDIATE MEDICAL ATTENTION AND SPECIAL TREATMENT NEEDED:

PROVIDE GENERAL SUPPORTIVE MEASURES AND TREAT SYMPTOMATICALLY. KEEP VICTIM UNDER OBSERVATION. SYMPTOMS MAY BE DELAYED.

GENERAL INFORMATION:

ENSURE THAT MEDICAL PERSONNEL ARE AWARE OF THE MATERIAL(S) INVOLVED, AND TAKE PRECAUTIONS TO PROTECT THEMSELVES.

5. FIRE-FIGHTING MEASURES

SUITABLE EXTINGUISHING MEDIA:
WATER FOG. FOAM. DRY CHEMICAL POWDER. DRY CHEMICALS. CARBON DIOXIDE (CO2).

UNSUITABLE EXTINGUISHING MEDIA:
DO NOT USE WATER JET AS AN EXTINGUISHER, AS THIS WILL SPREAD THE FIRE.

SPECIFIC HAZARDS ARISING FROM THE CHEMICAL:
PRESSURIZED CONTAINER MAY RUPTURE WHEN EXPOSED TO HEAT OR FLAME. DURING
FIRE, GASES HAZARDOUS TO HEALTH MAY BE FORMED.

SPECIAL PROTECTIVE EQUIPMENT AND PRECAUTIONS FOR FIREFIGHTERS:
SELF-CONTAINED BREATHING APPARATUS AND FULL PROTECTIVE CLOTHING MUST BE
WORN IN CASE OF FIRE.

FIRE-FIGHTING EQUIPMENT/INSTRUCTIONS:
IN CASE OF FIRE:
STOP LEAK IF SAFE TO DO SO. MOVE CONTAINERS FROM FIRE AREA IF YOU CAN DO SO
WITHOUT RISK. COOL CONTAINERS EXPOSED TO HEAT WITH WATER SPRAY AND REMOVE
CONTAINER, IF NO RISK IS INVOLVED. CONTAINERS SHOULD BE COOLED WITH WATER
TO PREVENT VAPOR PRESSURE BUILD UP.

GENERAL FIRE HAZARDS:
COMBUSTIBLE. CONTENTS UNDER PRESSURE. PRESSURIZED CONTAINER MAY RUPTURE
WHEN EXPOSED TO HEAT OR FLAME.

6. ACCIDENTAL RELEASE MEASURES



PERSONAL PRECAUTIONS, PROTECTIVE EQUIPMENT AND EMERGENCY PROCEDURES:
KEEP UNNECESSARY PERSONNEL AWAY. KEEP PEOPLE AWAY FROM AND UPWIND OF
SPILL/LEAK. KEEP OUT OF LOW AREAS. MANY VAPORS ARE HEAVIER THAN AIR AND
WILL SPREAD ALONG GROUND AND COLLECT IN LOW OR CONFINED AREAS (SEWERS,
BASEMENTS, TANKS). WEAR APPROPRIATE PROTECTIVE EQUIPMENT AND CLOTHING
DURING CLEAN-UP. EMERGENCY PERSONNEL NEED SELF-CONTAINED BREATHING
EQUIPMENT. DO NOT TOUCH DAMAGED CONTAINERS OR SPILLED MATERIAL UNLESS
WEARING APPROPRIATE PROTECTIVE CLOTHING. VENTILATE CLOSED SPACES BEFORE
ENTERING THEM. LOCAL AUTHORITIES SHOULD BE ADVISED IF SIGNIFICANT SPILLAGES
CANNOT BE CONTAINED. FOR PERSONAL PROTECTION, SEE SECTION 8 OF THE SDS.

METHODS AND MATERIALS FOR CONTAINMENT AND CLEANING UP:
ELIMINATE ALL IGNITION SOURCES (NO SMOKING, FLARES, SPARKS, OR FLAMES IN
IMMEDIATE AREA). KEEP COMBUSTIBLES (WOOD, PAPER, OIL, ETC.) AWAY FROM
SPILLED MATERIAL. STOP THE FLOW OF MATERIAL, IF THIS IS WITHOUT RISK.
PREVENT PRODUCT FROM ENTERING DRAINS. WIPE UP WITH ABSORBENT MATERIAL
(E.G. CLOTH, FLEECE). CLEAN SURFACE THOROUGHLY TO REMOVE RESIDUAL
CONTAMINATION. FOR WASTE DISPOSAL, SEE SECTION 13 OF THE SDS.

ENVIRONMENTAL PRECAUTIONS:
AVOID RELEASE TO THE ENVIRONMENT. PREVENT FURTHER LEAKAGE OR SPILLAGE IF
SAFE TO DO SO. AVOID DISCHARGE INTO DRAINS, WATER COURSES OR ONTO THE
GROUND. INFORM APPROPRIATE MANAGERIAL OR SUPERVISORY PERSONNEL OF ALL
ENVIRONMENTAL RELEASES.

7. HANDLING AND STORAGE



PRECAUTIONS FOR SAFE HANDLING:

PRESSURIZED CONTAINER:
DO NOT PIERCE OR BURN, EVEN AFTER USE. DO NOT USE IF SPRAY BUTTON IS

MISSING OR DEFECTIVE. DO NOT SPRAY ON A NAKED FLAME OR ANY OTHER INCANDESCENT MATERIAL. DO NOT SMOKE WHILE USING OR UNTIL SPRAYED SURFACE IS THOROUGHLY DRY. DO NOT CUT, WELD, SOLDER, DRILL, GRIND, OR EXPOSE CONTAINERS TO HEAT, FLAME, SPARKS, OR OTHER SOURCES OF IGNITION. USE CAUTION AROUND ENERGIZED EQUIPMENT. THE METAL CONTAINER WILL CONDUCT ELECTRICITY IF IT CONTACTS A LIVE SOURCE. THIS MAY RESULT IN INJURY TO THE USER FROM ELECTRICAL SHOCK AND/OR FLASH FIRE. DO NOT GET THIS MATERIAL IN CONTACT WITH EYES. USE ONLY IN WELL-VENTILATED AREAS. WEAR APPROPRIATE PERSONAL PROTECTIVE EQUIPMENT. OBSERVE GOOD INDUSTRIAL HYGIENE PRACTICES. AVOID RELEASE TO THE ENVIRONMENT. FOR PRODUCT USAGE INSTRUCTIONS, PLEASE SEE THE PRODUCT LABEL.

CONDITIONS FOR SAFE STORAGE, INCLUDING ANY INCOMPATIBILITIES:
LEVEL 1 AEROSOL.

CONTENTS UNDER PRESSURE. DO NOT EXPOSE TO HEAT OR STORE AT TEMPERATURES ABOVE 120 DEG. F/49 DEG. C AS CAN MAY BURST. DO NOT PUNCTURE, INCINERATE OR CRUSH. DO NOT HANDLE OR STORE NEAR AN OPEN FLAME, HEAT OR OTHER SOURCES OF IGNITION. STORE IN A WELL-VENTILATED PLACE. STORE AWAY FROM INCOMPATIBLE MATERIALS (SEE SECTION 10 OF THE SDS).

8. EXPOSURE CONTROLS/PERSONAL PROTECTION



OCCUPATIONAL EXPOSURE LIMITS:

US. OSHA TABLE Z-1 LIMITS FOR AIR CONTAMINANTS (29 CFR 1910.1000):

COMPONENTS	TYPE	VALUE	FORM
LIGHT MINERAL OIL (CAS 8042-47-5)	PEL	5 MG/M3	MIST.

US. ACGIH THRESHOLD LIMIT VALUES:

COMPONENTS	TYPE	VALUE	FORM
LIGHT MINERAL OIL (CAS 8042-47-5)	TWA	5 MG/M3	INHALABLE FRACTION.

US. NIOSH: POCKET GUIDE TO CHEMICAL HAZARDS

COMPONENTS	TYPE	VALUE	FORM
DISTILLATES (PETROLEUM), HYDROTREATED LIGHT (CAS 64742-47-8)	TWA	100 MG/M3	
LIGHT MINERAL OIL (CAS 8042-47-5)	STEL	10 MG/M3	MIST.
	TWA	5 MG/M3	MIST.

BIOLOGICAL LIMIT VALUES:

NO BIOLOGICAL EXPOSURE LIMITS NOTED FOR THE INGREDIENT(S).

APPROPRIATE ENGINEERING CONTROLS:

GOOD GENERAL VENTILATION (TYPICALLY 10 AIR CHANGES PER HOUR) SHOULD BE USED. VENTILATION RATES SHOULD BE MATCHED TO CONDITIONS. IF APPLICABLE, USE PROCESS ENCLOSURES, LOCAL EXHAUST VENTILATION, OR OTHER ENGINEERING CONTROLS TO MAINTAIN AIRBORNE LEVELS BELOW RECOMMENDED EXPOSURE LIMITS. IF EXPOSURE LIMITS HAVE NOT BEEN ESTABLISHED, MAINTAIN AIRBORNE LEVELS TO AN ACCEPTABLE LEVEL. PROVIDE EYEWASH STATION.

INDIVIDUAL PROTECTION MEASURES, SUCH AS PERSONAL PROTECTIVE EQUIPMENT:

EYE/FACE PROTECTION:

WEAR SAFETY GLASSES WITH SIDE SHIELDS (OR GOGGLES) AND A FACE SHIELD.

SKIN PROTECTION:**HAND PROTECTION:**

WEAR PROTECTIVE GLOVES SUCH AS: NITRILE. POLYVINYL CHLORIDE (PVC).

OTHER: WEAR SUITABLE PROTECTIVE CLOTHING.

RESPIRATORY PROTECTION:

IF ENGINEERING CONTROLS ARE NOT FEASIBLE OR IF EXPOSURE EXCEEDS THE APPLICABLE EXPOSURE LIMITS, USE A NIOSH-APPROVED CARTRIDGE RESPIRATOR WITH AN ORGANIC VAPOR CARTRIDGE. USE A SELF-CONTAINED BREATHING APPARATUS IN CONFINED SPACES AND FOR EMERGENCIES. AIR MONITORING IS NEEDED TO DETERMINE ACTUAL EMPLOYEE EXPOSURE LEVELS.

THERMAL HAZARDS:

WEAR APPROPRIATE THERMAL PROTECTIVE CLOTHING, WHEN NECESSARY.

GENERAL HYGIENE CONSIDERATIONS:

WHEN USING DO NOT SMOKE. ALWAYS OBSERVE GOOD PERSONAL HYGIENE MEASURES, SUCH AS WASHING AFTER HANDLING THE MATERIAL AND BEFORE EATING, DRINKING, AND/OR SMOKING. ROUTINELY WASH WORK CLOTHING AND PROTECTIVE EQUIPMENT TO REMOVE CONTAMINANTS.

9. PHYSICAL AND CHEMICAL PROPERTIES**APPEARANCE:**

PHYSICAL STATE: LIQUID.

FORM: AEROSOL.

COLOR: MILKY WHITE.

ODOR: MILD PETROLEUM.

ODOR THRESHOLD: NOT AVAILABLE.

PH: 10.5

MELTING POINT/FREEZING POINT: -74.2 DEG. F (-59 DEG. C) ESTIMATED

INITIAL BOILING POINT AND BOILING RANGE: 212 DEG. F (100 DEG. C) ESTIMATED

FLASH POINT: NONE (TAG CLOSED CUP)

EVAPORATION RATE: SLOW.

FLAMMABILITY (SOLID, GAS): NOT AVAILABLE.

UPPER/LOWER FLAMMABILITY OR EXPLOSIVE LIMITS:

FLAMMABILITY LIMIT - LOWER (%): 0.6% ESTIMATED

FLAMMABILITY LIMIT - UPPER (%): 23.5% ESTIMATED

VAPOR PRESSURE: 313.5 HPA ESTIMATED

VAPOR DENSITY: NOT AVAILABLE.

RELATIVE DENSITY: 0.92 ESTIMATED

SOLUBILITY (WATER): SOLUBLE.

PARTITION COEFFICIENT (N-OCTANOL/WATER): NOT AVAILABLE.

AUTO-IGNITION TEMPERATURE: 456.8 DEG. F (236 DEG. C) ESTIMATED

DECOMPOSITION TEMPERATURE: NOT AVAILABLE.

VISCOSITY (KINEMATIC): NOT AVAILABLE.

PERCENT VOLATILE: 94.6% ESTIMATED

10. STABILITY AND REACTIVITY



REACTIVITY:

THE PRODUCT IS STABLE AND NON-REACTIVE UNDER NORMAL CONDITIONS OF USE, STORAGE AND TRANSPORT.

CHEMICAL STABILITY: MATERIAL IS STABLE UNDER NORMAL CONDITIONS.

POSSIBILITY OF HAZARDOUS REACTIONS:

NO DANGEROUS REACTION KNOWN UNDER CONDITIONS OF NORMAL USE.

CONDITIONS TO AVOID:

HEAT, FLAMES AND SPARKS. CONTACT WITH INCOMPATIBLE MATERIALS.

INCOMPATIBLE MATERIALS: STRONG OXIDIZING AGENTS.

HAZARDOUS DECOMPOSITION PRODUCTS: CARBON OXIDES.

11. TOXICOLOGICAL INFORMATION



INFORMATION ON LIKELY ROUTES OF EXPOSURE:

INHALATION:

PROLONGED OR EXCESSIVE INHALATION MAY CAUSE RESPIRATORY TRACT IRRITATION.

SKIN CONTACT: PROLONGED SKIN CONTACT MAY CAUSE TEMPORARY IRRITATION.

EYE CONTACT: CAUSES SERIOUS EYE DAMAGE.

INGESTION:

INGESTION OF LARGE AMOUNTS MAY PRODUCE GASTROINTESTINAL DISTURBANCES INCLUDING IRRITATION, NAUSEA, AND DIARRHEA.

SYMPTOMS RELATED TO THE PHYSICAL, CHEMICAL AND TOXICOLOGICAL CHARACTERISTICS:

SEVERE EYE IRRITATION. SYMPTOMS MAY INCLUDE STINGING, TEARING, REDNESS, SWELLING, AND BLURRED VISION. PERMANENT EYE DAMAGE INCLUDING BLINDNESS COULD RESULT.

INFORMATION ON TOXICOLOGICAL EFFECTS:

ACUTE TOXICITY: NOT AVAILABLE.

PRODUCT	SPECIES	TEST RESULTS
---------	---------	--------------

HYDROFORCE (R*) STAINLESS STEEL CLEANER AND POLISH:

ACUTE:

DERMAL:
LD50 RABBIT 6792 MG/KG ESTIMATED

INHALATION:
LC50 RAT 11088 MG/L, 4 HOURS ESTIMATED

ORAL:
LD50 RAT 14236 MG/KG ESTIMATED

*ESTIMATES FOR PRODUCT MAY BE BASED ON ADDITIONAL COMPONENT DATA NOT SHOWN.

SKIN CORROSION/IRRITATION:
PROLONGED SKIN CONTACT MAY CAUSE TEMPORARY IRRITATION.

SERIOUS EYE DAMAGE/EYE IRRITATION: CAUSES SERIOUS EYE DAMAGE.

RESPIRATORY SENSITIZATION: NOT A RESPIRATORY SENSITIZER.

SKIN SENSITIZATION:
THIS PRODUCT IS NOT EXPECTED TO CAUSE SKIN SENSITIZATION.

GERM CELL MUTAGENICITY:
NO DATA AVAILABLE TO INDICATE PRODUCT OR ANY COMPONENTS PRESENT AT GREATER THAN 0.1% ARE MUTAGENIC OR GENOTOXIC.

CARCINOGENICITY:
BASED ON AVAILABLE DATA, THE CLASSIFICATION CRITERIA ARE NOT MET.

IARC MONOGRAPHS. OVERALL EVALUATION OF CARCINOGENICITY:

LIGHT MINERAL OIL (CAS 8042-47-5):
3 NOT CLASSIFIABLE AS TO CARCINOGENICITY TO HUMANS.

REPRODUCTIVE TOXICITY:
THIS PRODUCT IS NOT EXPECTED TO CAUSE REPRODUCTIVE OR DEVELOPMENTAL EFFECTS.

SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE: NOT CLASSIFIED.

SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE: NOT CLASSIFIED.

ASPIRATION HAZARD:
BASED ON AVAILABLE DATA, THE CLASSIFICATION CRITERIA ARE NOT MET.

CHRONIC EFFECTS: PROLONGED EXPOSURE MAY CAUSE CHRONIC EFFECTS.

12. ECOLOGICAL INFORMATION



ECOTOXICITY: HARMFUL TO AQUATIC LIFE WITH LONG LASTING EFFECTS.

PRODUCT	SPECIES	TEST RESULTS
---------	---------	--------------

HYDROFORCE (R*) STAINLESS STEEL CLEANER AND POLISH:

AQUATIC:

ACUTE:

CRUSTACEA	EC50	DAPHNIA	1144.0269 MG/L, 48 HOURS ESTIMATED
-----------	------	---------	------------------------------------

FISH	LC50	FISH	1546.4788 MG/L, 96 HOURS
------	------	------	--------------------------

ESTIMATED

COMPONENTS		SPECIES	TEST RESULTS
DIOCTYL SODIUM SULFOSUCCINATE (CAS 577-11-7):			
AQUATIC:			
FISH	LC50	RAINBOW TROUT, DONALDSON TROUT (ONCORHYNCHUS MYKISS)	20 - 40 MG/L, 96 HOURS

*ESTIMATES FOR PRODUCT MAY BE BASED ON ADDITIONAL COMPONENT DATA NOT SHOWN.

PERSISTENCE AND DEGRADABILITY:
NO DATA IS AVAILABLE ON THE DEGRADABILITY OF THIS PRODUCT.

BIOACCUMULATIVE POTENTIAL:

MOBILITY IN SOIL: NO DATA AVAILABLE.

OTHER ADVERSE EFFECTS:
NO OTHER ADVERSE ENVIRONMENTAL EFFECTS (E.G. OZONE DEPLETION, PHOTOCHEMICAL OZONE CREATION POTENTIAL, ENDOCRINE DISRUPTION, GLOBAL WARMING POTENTIAL) ARE EXPECTED FROM THIS COMPONENT.

13. DISPOSAL CONSIDERATIONS



DISPOSAL OF WASTE FROM RESIDUES / UNUSED PRODUCTS:
THE DISPENSED LIQUID PRODUCT IS NOT A RCRA HAZARDOUS WASTE (SEE 40 CFR PART 261.20 - 261.33). EMPTY CONTAINER CAN BE RECYCLED. COLLECT AND RECLAIM OR DISPOSE IN SEALED CONTAINERS AT LICENSED WASTE DISPOSAL SITE. CONTENTS UNDER PRESSURE. DO NOT PUNCTURE, INCINERATE OR CRUSH. DO NOT ALLOW THIS MATERIAL TO DRAIN INTO SEWERS/WATER SUPPLIES. DO NOT CONTAMINATE PONDS, WATERWAYS OR DITCHES WITH CHEMICAL OR USED CONTAINER. DISPOSE IN ACCORDANCE WITH ALL APPLICABLE REGULATIONS.

HAZARDOUS WASTE CODE: NOT REGULATED.

CONTAMINATED PACKAGING:
EMPTY CONTAINERS SHOULD BE TAKEN TO AN APPROVED WASTE HANDLING SITE FOR RECYCLING OR DISPOSAL. SINCE EMPTIED CONTAINERS MAY RETAIN PRODUCT RESIDUE, FOLLOW LABEL WARNINGS EVEN AFTER CONTAINER IS EMPTIED.

14. TRANSPORT INFORMATION



DOT:

UN NUMBER: UN1950

UN PROPER SHIPPING NAME: AEROSOLS, NON-FLAMMABLE, LIMITED QUANTITY

TRANSPORT HAZARD CLASS(ES):

CLASS: 2.2

SUBSIDIARY RISK:

LABEL(S): 2.2

PACKING GROUP: NOT APPLICABLE.

SPECIAL PRECAUTIONS FOR USER:
READ SAFETY INSTRUCTIONS, SDS AND EMERGENCY PROCEDURES BEFORE HANDLING.

SPECIAL PROVISIONS: NOT AVAILABLE.

PACKAGING EXCEPTIONS: 306

PACKAGING NON BULK: NONE

PACKAGING BULK: NONE

IATA:

UN NUMBER: UN1950

UN PROPER SHIPPING NAME: AEROSOLS, NON-FLAMMABLE, LIMITED QUANTITY

TRANSPORT HAZARD CLASS(ES):

CLASS: 2.2

SUBSIDIARY RISK:

PACKING GROUP: NOT APPLICABLE.

ENVIRONMENTAL HAZARDS: NO.

ERG CODE: 2L

SPECIAL PRECAUTIONS FOR USER:
READ SAFETY INSTRUCTIONS, SDS AND EMERGENCY PROCEDURES BEFORE HANDLING.

OTHER INFORMATION:

PASSENGER AND CARGO AIRCRAFT: ALLOWED.

CARGO AIRCRAFT ONLY: ALLOWED.

IMDG:

UN NUMBER: UN1950

UN PROPER SHIPPING NAME: AEROSOLS, LIMITED QUANTITY

TRANSPORT HAZARD CLASS(ES):

CLASS: 2

SUBSIDIARY RISK:

PACKING GROUP: NOT APPLICABLE.

ENVIRONMENTAL HAZARDS:

MARINE POLLUTANT: NO.

EMS: NOT AVAILABLE.

SPECIAL PRECAUTIONS FOR USER:
READ SAFETY INSTRUCTIONS, SDS AND EMERGENCY PROCEDURES BEFORE HANDLING.

15. REGULATORY INFORMATION



US FEDERAL REGULATIONS:

THIS PRODUCT IS A "HAZARDOUS CHEMICAL" AS DEFINED BY THE OSHA HAZARD COMMUNICATION STANDARD, 29 CFR 1910.1200.

TSCA SECTION 12(B) EXPORT NOTIFICATION (40 CFR 707, SUBPT. D):
NOT REGULATED.

US. OSHA SPECIFICALLY REGULATED SUBSTANCES (29 CFR 1910.1001-1050):

NOT LISTED.

SARA 304 EMERGENCY RELEASE NOTIFICATION: NOT REGULATED.

US EPCRA (SARA TITLE III) SECTION 313 - LISTED SUBSTANCE
TOXIC CHEMICAL

NOT LISTED.

CERCLA HAZARDOUS SUBSTANCE LIST (40 CFR 302.4): NOT LISTED.

CERCLA HAZARDOUS SUBSTANCES REPORTABLE QUANTITY

NOT LISTED.

SPILLS OR RELEASES RESULTING IN THE LOSS OF ANY INGREDIENT AT OR ABOVE
ITS RQ REQUIRE IMMEDIATE NOTIFICATION TO THE NATIONAL RESPONSE CENTER
(800-424-8802) AND TO YOUR LOCAL EMERGENCY PLANNING COMMITTEE.

CLEAN AIR ACT (CAA) SECTION 112 HAZARDOUS AIR POLLUTANTS (HAPS) LIST:
NOT REGULATED.

CLEAN AIR ACT (CAA) SECTION 112(R) ACCIDENTAL RELEASE PREVENTION (40 CFR
68.130): NOT REGULATED.

SAFE DRINKING WATER ACT (SDWA): NOT REGULATED.

FOOD AND DRUG ADMINISTRATION (FDA): NOT REGULATED.

SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT OF 1986 (SARA):
SECTION 311/312 HAZARD CATEGORIES:

IMMEDIATE HAZARD: YES

DELAYED HAZARD: NO

FIRE HAZARD: NO

PRESSURE HAZARD: YES

REACTIVITY HAZARD: NO

SARA 302 EXTREMELY HAZARDOUS SUBSTANCE: NO

US STATE REGULATIONS:

US. CALIFORNIA. CANDIDATE CHEMICALS LIST. SAFER CONSUMER PRODUCTS
REGULATIONS (CAL. CODE REGS, TIT. 22, 69502.3, SUBD. (A)):
LIQUEFIED PETROLEUM GAS (CAS 68476-86-8)
DISTILLATES (PETROLEUM), HYDROTREATED LIGHT (CAS 64742-47-8)

US. CALIFORNIA CONTROLLED SUBSTANCES. CA DEPARTMENT OF JUSTICE
(CALIFORNIA HEALTH AND SAFETY CODE SECTION 11100): NOT LISTED.

US. NEW JERSEY WORKER AND COMMUNITY RIGHT-TO-KNOW ACT:
LIGHT MINERAL OIL (CAS 8042-47-5)

US. MASSACHUSETTS RTK - SUBSTANCE LIST:
LIGHT MINERAL OIL (CAS 8042-47-5)

US. PENNSYLVANIA WORKER AND COMMUNITY RIGHT-TO-KNOW LAW:
LIGHT MINERAL OIL (CAS 8042-47-5)

US. RHODE ISLAND RTK: NONE.

US. CALIFORNIA PROPOSITION 65:

WARNING:

THIS PRODUCT CONTAINS A CHEMICAL KNOWN TO THE STATE OF CALIFORNIA TO CAUSE
CANCER.

US - CALIFORNIA PROPOSITION 65 - CRT LISTED DATE/CARCINOGENIC SUBSTANCE
 1,3-DICHLOROPROPENE (CAS 542-75-6) LISTED: JANUARY 1, 1989
 DIETHANOLAMINE (CAS 111-42-2) LISTED: JUNE 22, 2012
 METHYLENE CHLORIDE (CAS 75-09-2) LISTED: APRIL 1, 1988

VOLATILE ORGANIC COMPOUNDS (VOC) REGULATIONS:

EPA:

VOC CONTENT (40 CFR 51.100(S)): 35.2%
 CONSUMER PRODUCTS (40 CFR 59, SUBPT. C): NOT REGULATED

STATE:

CONSUMER PRODUCTS:

THIS PRODUCT IS REGULATED AS A METAL POLISH OR CLEANSER (AEROSOL).
 THIS PRODUCT IS COMPLIANT FOR USE IN ALL 50 STATES.

VOC CONTENT (CA): 14.5%
 VOC CONTENT (OTC): 14.5%

INTERNATIONAL INVENTORIES:

COUNTRY (S) OR REGION	INVENTORY NAME	ON INVENTORY (YES/NO) *
AUSTRALIA	AUSTRALIAN INVENTORY OF CHEMICAL SUBSTANCES (AICS)	NO
CANADA	DOMESTIC SUBSTANCES LIST (DSL)	NO
CANADA	NON-DOMESTIC SUBSTANCES LIST (NDSL)	YES
CHINA	INVENTORY OF EXISTING CHEMICAL SUBSTANCES IN CHINA (IECSC)	YES
EUROPE	EUROPEAN INVENTORY OF EXISTING COMMERCIAL CHEMICAL SUBSTANCES (EINECS)	NO
EUROPE	EUROPEAN LIST OF NOTIFIED CHEMICAL SUBSTANCES (ELINCS)	NO
JAPAN	INVENTORY OF EXISTING AND NEW CHEMICAL SUBSTANCES (ENCS)	NO
KOREA	EXISTING CHEMICALS LIST (ECL)	NO
NEW ZEALAND	NEW ZEALAND INVENTORY	NO
PHILIPPINES	PHILIPPINE INVENTORY OF CHEMICALS AND CHEMICAL SUBSTANCES (PICCS)	NO
UNITED STATES & PUERTO RICO	TOXIC SUBSTANCES CONTROL ACT (TSCA) INVENTORY	YES

*A "YES" INDICATES THAT ALL COMPONENTS OF THIS PRODUCT COMPLY WITH THE
 INVENTORY REQUIREMENTS ADMINISTERED BY THE GOVERNING COUNTRY(S)

A "NO" INDICATES THAT ONE OR MORE COMPONENTS OF THE PRODUCT ARE NOT LISTED
 OR EXEMPT FROM LISTING ON THE INVENTORY ADMINISTERED BY THE GOVERNING
 COUNTRY(S).

16. OTHER INFORMATION, INCLUDING DATE OF PREPARATION

OR LAST REVISION

ISSUE DATE: 04-30-2015

PREPARED BY: ALLISON CHO

VERSION #: 01

FURTHER INFORMATION: CRC # 925B

HMIS (R*) RATINGS:

HEALTH	3
FLAMMABILITY	1
PHYSICAL HAZARD	0
PERSONAL PROTECTION	D

NFPA RATINGS:

HEALTH	3
FLAMMABILITY	1
INSTABILITY	0

NFPA RATINGS:

3
1
0

DISCLAIMER:

THE INFORMATION CONTAINED IN THIS DOCUMENT APPLIES TO THIS SPECIFIC MATERIAL AS SUPPLIED. IT MAY NOT BE VALID FOR THIS MATERIAL IF IT IS USED IN COMBINATION WITH ANY OTHER MATERIALS. THIS INFORMATION IS ACCURATE TO THE BEST OF CRC INDUSTRIES' KNOWLEDGE OR OBTAINED FROM SOURCES BELIEVED BY CRC TO BE ACCURATE. BEFORE USING ANY PRODUCT, READ ALL WARNINGS AND DIRECTIONS ON THE LABEL. FOR FURTHER CLARIFICATION OF ANY INFORMATION CONTAINED ON THIS (M)SDS CONSULT YOUR SUPERVISOR, A HEALTH & SAFETY PROFESSIONAL, OR CRC INDUSTRIES.

MATERIAL NAME: HYDROFORCE (R*) STAINLESS STEEL CLEANER AND POLISH

SDS: US